K1378_AG

Five lobe grips plastic lockable with external thread



Item description/product images



Description

Version:

Grip black gray RAL 7021 or red similar to RAL 3020. Steel parts trivalent blue passivated. Stainless steel bright.


Note:

Lockable five lobe grips prevent unauthorised loosening of the screw connection. The cylinder lock styles a positive lock between grip and screw. When unlocked the grip rotates freely without driving the screw, preventing unauthorised opening of the screw connection.

The lockable five lobe grips are supplied with 2 keys each. The key can be removed in the open and closed position. The locks are a single-key system, i.e. the same key works in all locks.

On request:

Other versions.



Order No.	Component	Main	D	D1	D2	Н	H1	L
	material	color						
K1378.6808X20	steel	black grey	M8	68	24	10	45,5	20
K1378.6810X20	steel	black grey	M10	68	24	10	45,5	20
K1378.06808X20	stainless steel	black grey	M8	68	24	10	45,5	20
K1378.06810X20	stainless steel	black grey	M10	68	24	10	45,5	20
K1378.846808X20	steel	red	M8	68	24	10	45,5	20
K1378.846810X20	steel	red	M10	68	24	10	45,5	20
K1378.0846808X20	stainless steel	red	M8	68	24	10	45,5	20
K1378.0846810X20	stainless steel	red	M10	68	24	10	45,5	20

Drawings



Five lobe grips plastic lockable with external thread

