

Cam levers, steel, adjustable with external thread, plastic thrust washer and steel stud - inch

Item description/product images

INCH
Parts



Description

Product description:

These cam levers have a technically optimised plastic thrust washer.

The thrust washer is made of a special high-performance plastic that guarantees very good wear and creep resistance.

Material:

Handle steel 1.0401.

Thrust washer high performance, carbon-fibre reinforced thermoplastic.

Hinge pin stainless steel 1.4305 (AISI 303 equivalent).

Stud steel, grade 5.8.

Version:

Handle and stud blue passivated.

Thrust washer, black.

Hinge pin bright.

Note:

Adjustable cam levers are used if the position of the lever relative to the axis of tension only permits one specific position (interference circle). The exact position of the lever is adjusted using a screwdriver on the fine thread setscrew.

Plastics are subject to creeping under load (retardation).

Accessory:

For slightly curved contact faces, a stainless steel washer K2130 can also be ordered.


This washer can be mounted between the thrust washer and the contact face.

Drawing reference:

1) setscrew for fine adjustment of lever

Cam levers, steel, adjustable with external thread, plastic thrust washer and steel stud - inch

Drawings



Cam levers, adjustable, external thread, steel

Order No.	D	D1	D2	B	B1	H	H1	A	A1	L	Travel S	Clamping force F (kN)	Hand force FH N
K2128.15022A1X20	10-32	16	9	21,5	15	14,7	22,2	70,4	79,2	20	1,2	4	120
K2128.15022A1X30	10-32	16	9	21,5	15	14,7	22,2	70,4	79,2	30	1,2	4	120
K2128.15022A1X40	10-32	16	9	21,5	15	14,7	22,2	70,4	79,2	40	1,2	4	120
K2128.15022A1X50	10-32	16	9	21,5	15	14,7	22,2	70,4	79,2	50	1,2	4	120
K2128.15022A2X20	1/4-20	16	9	21,5	15	14,7	22,2	70,4	79,2	20	1,2	4	120
K2128.15022A2X30	1/4-20	16	9	21,5	15	14,7	22,2	70,4	79,2	30	1,2	4	120
K2128.15022A2X40	1/4-20	16	9	21,5	15	14,7	22,2	70,4	79,2	40	1,2	4	120
K2128.15022A2X50	1/4-20	16	9	21,5	15	14,7	22,2	70,4	79,2	50	1,2	4	120
K2128.25022A3X25	5/16-18	25	11	33,3	24	18,3	28,8	96	108	25	1,5	8	350
K2128.25022A3X30	5/16-18	25	11	33,3	24	18,3	28,8	96	108	30	1,5	8	350
K2128.25022A3X40	5/16-18	25	11	33,3	24	18,3	28,8	96	108	40	1,5	8	350
K2128.25022A3X50	5/16-18	25	11	33,3	24	18,3	28,8	96	108	50	1,5	8	350
K2128.25022A4X25	3/8-16	25	11	33,3	24	18,3	28,8	96	108	25	1,5	8	350
K2128.25022A4X30	3/8-16	25	11	33,3	24	18,3	28,8	96	108	30	1,5	8	350
K2128.25022A4X40	3/8-16	25	11	33,3	24	18,3	28,8	96	108	40	1,5	8	350
K2128.25022A4X50	3/8-16	25	11	33,3	24	18,3	28,8	96	108	50	1,5	8	350

Cam levers, steel, adjustable with external thread, plastic thrust washer and steel stud - inch

